



LOOSEBOX / LYING AREA

BELMONDO® Classic

**„The Classic“ –
also for higher stress areas**

- enhanced slip resistance due to appropriate softness and elasticity
- heat insulation and noise reduction
- gentle on hooves and joints
- solid, vulcanised rubber does not absorb any moisture
- minimizes the amount of bedding, costs and labour
- suitable for vehicle traffic*


Surface:	horseshoe profile with wear resistant top coat
Lower side:	grooves
Material:	rubber
Thickness:	18 mm
Dimensions:	1 m x 1 m
Weight:	approx. 21 kg
Puzzle shaped edges:	on 4 sides




For every type of shoe.



PRÜFNUMMER
201501002



**horseshoe profile
with top coat**



**stable groove profile
on lower side**

* can be driven on with standard equipment such as farm yard loader or tractor with authorized pneumatic tyres at the recommended inflation pressure up to max. 4 bar. (Notice: drive with due care and steer in large radius!)

Special dimensions are generally available on request.

All BELMONDO® products are suitable for looseboxes as well as open stables.

Despite good interlocking puzzle pieces, remaining liquid / urine could seep into the seams. To bind fluids, hence, a small amount of absorbent bedding is always required in the loosebox. We also recommend a minimal amount of bedding in the open stable.



Laying: according to BELMONDO® laying instructions

Tolerances: thickness: +3/-2 mm
length/width: +/- 1.5 % (DIN ISO 3302-1 tolerance class M4)
The tolerances also apply within the mat.

The products presented here should only be used for the listed applications. Technical specifications are subject to alterations. All sales are subject to our General Terms and Conditions. Legal basis is the German version of the document.